

FLUID CAPACITIES

+ 3.0L Engine Gas High Output

- 3.0L Engine Gas Standard Output

Description	Capacities	Type	Part Number	Global Part Number
Engine Oil With Filter	7.5 Quarts / 7.1 Liters	We recommend using Mopar® SAE 0W-20 Full Synthetic Engine Oil, which meets the requirements of the manufacturer Material Standard MS-6395. Equivalent full synthetic SAE 0W-20 engine oil can be used but must have the API Starburst trademark with a certification level of API-SP or later Ú page 315. API-SN+ is also acceptable.	68523994AA	68523994GA
Cooling System *	Engine - 16.17 Quarts / 15.3 Liters	We recommend you use Mopar® Antifreeze/Coolant 10 Year/150,000 Mile (240,000 km) Formula OAT (Organic Additive Technology) meeting the requirements of the manufacturer Material Standard MS.90032.	68163848AB	68163848GB
	Engine w/Axle Oil Heater - 18.49 Quarts / 17.5 Liters			
	Intercooler - 3.2 Quarts / 3.0 Liters			
Fuel Selection	1500 Regular Cab Shortbed/Crew Quad Cab Models: 23 Gallons / 87 Liters	87 Octane (R+M)/2 Method, 0-15% Ethanol.	-	-
	1500 Regular Cab Shortbed/Crew Quad Cab Models: 26 Gallons / 98 Liters			
	1500 Regular Cab Longbed/Crew Quad Cab Models (Optional): 33 Gallons / 121 Liters			

Description	Capacities	Type	Part Number	Global Part Number
Spark Plugs	GAP	We recommend you use MOPAR Spark Plugs.	68265438AB	–
	.028 in. / .70 mm			
* Includes heater and coolant reservoir filled to MAX level.				

 3.6L Engine

 A/C Refrigerant System

 Axles

 Chassis

 Transfer Case

 Transmission